

Features	TrailMAC	Camtrakker	Moultrie Game Watcher	Non Typical DC-200	Stealthcam MC2-B & MC2-BRT	TrailtimerEZ-2500 EZ-Cam™	Homebrew	WoodsWatcher	Highlander Photoscout
Camera	Canon SureShot BF or Owl PF 35 mm	Yashica T4 35 mm	Custom made 35 mm	Olympus Infinity XB 35 mm	Yashica Impression 35 mm	35mm camera, unknown model	Canon Owl PF 35mm camera	35 mm Samsung Maxima 33S Quartz	Canon LX II 35 mm
Camera Flash Range	35 feet	13 feet (ISO 100)	5 to 18 feet with ISO 400	Unknown at this time	10 ft for ISO 200; 14 ft ISO 400; 20 ft ISO 800	Unknown at this time	35 feet	9 feet	25 feet
Independent Camera Use	Yes	No	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Date/Time Stamp Options	month/day/year & day/hour/minute.	Day/month/year or day/hour/min	Date or time only option	Date/Time only	year/month/date or time	Date or Time only	5 options: year/month/date, day/time,month/time, year/time,year/month/time, no print	Day or time only	Day/time only
External Pic Number Indicator/Window	No, you have to open case to see camera	Yes, window on top. Digital display	No, have to open case	Yes, pushing switch has LED flash number of pics.	Yes LCD display window	Unknown	Yes	Yes, LED display	Yes, counts # of events/pics
Main Unit Battery	Eight "AA" alkalines	4 "C" alkalines, camera uses 1 3-volt lithium	2 each 9 volt alkalines	Two 9 volt alkaline	4 C cell alkalines	1 9 volt alkaline	1 each 9 volt alkaline battery	4 C alkalines	2 "AA" and 1 "9 volt" alkalines
Main Unit Battery Life	2 to 3 months Approximately	3 months Approximately	7 days	2 months approximately	21days	Unknown	Approximately 3 months depending on timer and sensor used	2 months approximately	3 to 6 months approximately
Camera Battery	Two AA alkalines	1 CR123A 3-volt lithium	Two AA alkalines	1 CR123A 3-volt lithium	2 AA alkalines	2 AA alkalines	2 AA alkalines	1 CR123A 3-volt lithium	2 AA alkalines
Low Battery Indicator	No	Main unit yes/camera - yes	Main unit no/camera - unknown	Yes, LED blinks battery condition	Yes	Yes	Optional	Main unit yes/camera unknown	Main unit no/ camera no
External On/Off Switch	Yes	Yes, push button with green LED indicator light	No	Yes, automatically turns on after 12 minutes.	On/test (standby)/off (reset) switch	Yes	Yes	Yes with 2 minute delay.	Yes, magnet switch
Detection Method & Range	Passive infrared	Passive infrared	Passive infrared	Passive infrared	Passive infrared	Passive infrared	Passive infrared	Passive infrared	Passive infrared
Delay Options	Seven time delay settings from 1 minute up to 2 hours	1 min. 5 min. or 20 min.	15 secs. to 30 minutes	10 position rotary camera delay switch with 15 seconds to 1 hour delay	1 to 60 minutes	1, 5 or 10 minute	Many depending on timer board used	8 settings between 10 seconds and 20 minutes	1 to 5 minute
Walk Test Light	Yes, LED	Yes, aiming laser	Yes	Yes	LED on front for walk test	Yes	Yes. Pushbutton laser or LED	Yes	Yes
Event Counter	No	Yes	No	Yes, 500 events	Yes, up to 99 events	Yes, 250 events	Optional	yes, 36 events	Yes
Operation Modes	24 hours a day or daytime only	Unknown at this time	24 hour only	24 hour only setting. Optional Expander gives you more options.	24 hour only	on/off, auto and night scene flash modes	Daytime, nighttime and 24 hours	24 hours only	Day, Night or 24 hours
Waterproof	Yes	Yes	Yes	Yes	No, water resistant	Yes	Yes	Yes	Yes
Mounting Setup	Unknown at this time	Laces with quick clips for adjustment	Ratchet strap	Security cable and internal screw hole	Tree screw mount & mounting strap	Adjustable strap with self alignment ribs	Mounting straps or bungees	2 hooks for bungee cord or chain	Ratchet strap
Size	105 cu. inches.	(w) 6.75" x (h) 10.3" x (d) 2.95"	12"w x 7"h x 10"d	6" w x 9 1/2" h x 2 1/2" d.	7-1/2"Lx6"Wx3"D.	Unknown at this time	Depends on which case you choose	6"w x 5" x 3.5"d	7"w x 9"h x 4"d
Weight	2 lbs.	38.5 oz.	Approximately 2 lbs.	Unknown at this time	Unknown at this time	Unknown at this time	Unknown at this time	1 lb. 15 ozs.	3 lbs.
Case	Weatherproof, impact resistant, and UV resistant polypropylene housing.	ABS plastic	ABS plastic.	ABS plastic.	Molded plastic	ABS plastic	Your choice of many	Lexan plastic	ABS plastic
Temperature Rating	Unknown at this time	minus 30 to 100 degrees F	Unit cannot be used below freezing	Unknown at this time	14 to 122 degrees Fahrenheit	Unknown at this time	0F to 110F	minus 30 to 100 degrees Fahrenheit	minus 30 to 100 degrees Fahrenheit
Camo	Realtree Hardwoods® HD™	Mossy Oak	No, black paint finish	Tree bark Reality® camo 3-D texturing	Realtree Hardwoods Green® HD™	TimberGhost™ Camo	Camo is up to you	Yes, camo paint finish	Yes, camo paint finish
Security Lock/Case	Steel Locking Bracket Available separately	Security cable and a small padlock	No	Security cable and internal screw hole	No	Yes, range on case for padlock	Your choice	2 hooks for cable or chain	2 latches for user supplied lock
Warranty	1 year	1 year parts and labor	1 year parts and labor	2 yr. electronics/ 1 year case \$ camera	1 year parts/labor	90 days	You fix it since you made it	3 year camera, 1 year on rest of unit	1 year parts and labor
Street Price	\$369.99	\$429.95	\$199.99	\$259.99	\$159.99	\$199.99	\$50 to \$100	\$275.00	\$349.99