

Features	TrailMAC	Camtraker	Penn's Woods	Cuddeback	Snapshot Sniper	Homebrew	ScoutPro	Game-Yu	Highlander
Camera	Olympus D-390 Digital Color Camera	Olympus D-390 Digital Color Camera	Olympus D-390 Digital Color Camera	Unknown Digital Color Camera	Olympus D-380 Color Camera	OlympusD-370, D-380 or D-390 Digital Color Camera	Olympus D-380 Digital Color Camera	Unknown black & white Webcam type camera	Unknown at this time
Camera Flash Range	Special Flash Enhancer for out to 30-Feet	10' (2.5m) ISO 100	10' (2.5m) ISO 100	25 foot	Special Flash Enhancer for out to 30-Feet.	8.2 ft.(2.5 m) ISO 100. Slave flash optional to 50 feet	8.2 ft.(2.5 m) ISO 100. Optional slave flash out to 50 feet	No flash since unit uses IR at night. 25 feet	No flash since unit uses IR at night
Image Media	32MB, 128MB, or 256MB XD-Picture Card	32MB, 128MB, or 256MB XD-Picture Card	32MB, 128MB, or 256MB XD-Picture Card	Smart Media Card storage 8M to 128M	8MB to 128MB SmartMedia Card	SmartMedia card (4, 8, 16, 32, 64 and 128 MB)	8MB to 128MB SmartMedia Card	Intel Strataflash flash memory	CompactFlash Type I & II flash card
Image Resolutions	2 Megapixel, 1,600 x 1,200	2.0-megapixel 1,600 x 1,200	2 Megapixel, 1,600 x 1,200	1.3 megapixel. 1078x768 pixels	2 Meg pixel, 1,600 x 1,200	1.3 megapixels. 1,280 X 960	2 Megapixel. 1,600 x 1,200	320 x 240	640 x 480
Image & Video Formats	EXIF 2.2 JPEG, DCF , QuickTime Motion JPEG Video at 320 x 240 (up to 15 seconds) or 160 x 120 (up to 60 seconds)	EXIF 2.2 JPEG, DCF , QuickTime Motion JPEG Video at 320 x 240 (up to 15 seconds) or 160 x 120 (up to 60 seconds)	EXIF 2.2 JPEG, DCF , QuickTime Motion JPEG Video at 320 x 240 (up to 15 seconds) or 160 x 120 (up to 60 seconds)	Image: EDIF 2.2 .JPG. Video is 160x120 pixels at 5 (FPS). Quicktime .MOV.	EXIF 2.2 JPEG, DCF , QuickTime Motion JPEG Video at 320 x 240 (up to 15 seconds) or 160 x 120 (up to 60 seconds)	JPG. QuickTimeTM Motion JPEG@.	EXIF 2.2 JPEG, DCF , QuickTime Motion JPEG Video at 320 x 240 (up to 15 seconds) or 160 x 120 (up to 60 seconds)	Unknown at this time	Unknown at this time
Inputs/Outputs	PCs and Macs via USB 1.1. NTSC video out for TV	PCs and Macs via USB 1.1. NTSC video out for TV	PCs and Macs via USB 1.1. NTSC video out for TV	Unknown at this time	PCs and Macs via USB 1.1. NTSC video out for TV	PCs and Macs via USB 1.1. NTSC video out for TV	PCs and Macs via USB 1.1. NTSC video out for TV	Optional hand-held monitor using the NTSC video output.	PCs and Macs via USB. NTSC video output for TV.
Independent Camera Use	Unknown at this time	Yes	Yes	Unknown at this time	Yes	Yes	Unknown at this time	No, Webcam type camera	No
Date/Time Stamp Options	Date/Time	Date/Time	Date/Time	Your name with time/date stamp	Date/Time	Date/Time	Date/Time	Time and day stamp	Day/time only
External Pic Number Indicator/Window	No, you have to open case to see camera	Unknown at this time	Unknown at this time	Unknown at this time	Unknown at this time	Yes	Unknown at this time	No	No
Main Unit Battery	Eight "AA" alkalines	2 external rechargeable sealed lead-acid battery packs	4 C cell alkaline	4 D-cell batteries	One 9 volt alkaline	1 each 9 volt alkaline battery	4 C alkalines	6 AA alkaline	6 "D" cell alkaline batteries
Main Unit Battery Life	3 months Approximately	Typically 3 months	30 days	Unknown at this time	Approx. 1 month	Approximately 3 months depending on timer used	1 month approximately	About 6 days	Unknown at this time
Camera Battery	Two AA alkalines or internal rechargeable lithium battery	Two AA alkaline or internal rechargeable lithium battery	Two AA alkalines	1 CR123A 3-volt lithium	2 AA alkalines	4 AA alkaline batteries	Two AA alkalines or internal rechargeable lithium battery	N/A	Unknown at this time
Low Battery Indicator	No	Unknown at this time	Unknown at this time,	Yes, LED blinks battery condition	Unknown at this time	Optional	Unknown at this time	Red LED	Unknown at this time
External On/Off Switch	Yes	Yes, push button with green LED indicator light	Unknown at this time	Yes	Unknown at this time	Yes	Yes	Yes	Yes
Detection Method & Range	Passive infrared. 3 sensitivity settings. Detection 60 Feet	Passive infrared. 60 feet	Passive infrared. 80 feet. Has sensitivity adjustment	Passive infrared. 100 feet	Passive infrared. 90 feet. Adj. daytime sensitivity	Passive infrared	Passive infrared	Active infrared. 25 feet	Passive infrared
Delay Options	Seven delay settings from 1 minute up to 2 hours (1,4,8,15,30,60 and 120 minutes).	6 settings, 20 second, 1 1/2, 3, 5, 25 or 45 minute delay.	Unknown at this time	1 minute up to 1 hour in minute increments	5 delay settings: 30 sec. 2 min. 5 min. 10 min. 30 min.	Many depending on timer board used	9 delays: 15 sec. 30 sec. 1, 3, 5, 10, 20, 30, 60 minutes	1 minute to 1 hour	1 or 5 minute
Walk Test Light	Yes, LED	Yes, aiming laser	Yes	Unknown at this time	Yes	Yes. Pushbutton laser or LED	Unknown at this time	With optional handheld TV, you see what the image will be	Yes
Event Counter	No	Unknown at this time	Unknown at this time	Yes, 475 events	Yes, 255 events	Optional	Unknown at this time	No	Yes, 1000 events
Operation Modes	24 hours a day or daytime only	24 hour, day-only or night-only operation	Daylight-only, nighttime-only or 24-hour operation	Day only, night only, all day or selected hours of day. Time lapse mode of 1 to 96 hours	Unknown at this time	Daytime, nighttime and 24 hours	Day, night or 24 hours	24 hours only	Day, Night or 24 hours
Waterproof	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Unknown at this time
Mounting Setup	Unknown at this time	Unknown at this time	Unknown at this time	Security cable and internal screw hole	Adjustable strap with self alignment ribs	Your choice	2 hooks for bungee cord or chain	Mounting strap. 2 mounting flanges with holes	None. User supplied
Size	Unknown at this time	(w) 6.75" x (h) 10.3" x (d) 2.95"	Unknown at this time	6" w x 9 1/2" h x 2 1/2"	Unknown at this time	Depends on which case you choose	Unknown at this time	Unknown at this time	Unknown at this time
Weight	Unknown at this time	38.5 oz.	Unknown at this time	Unknown at this time	Unknown at this time	Depends on which case you choose	Unknown at this time	Unknown at this time	Unknown at this time
Temperature Rating	Unknown at this time	Minus 30 to 100F degrees	Unknown at this time	Unknown at this time	Unknown at this time	Depends on PIR sensor and camera used	Unknown at this time	0 to 150 F degrees	Unknown at this time
Case	Weatherproof, impact resistant, and UV resistant polypropylene housing	ABS plastic	Gasketless, weatherproof housing ABS plastic	Gasketless, weatherproof housing ABS plastic	Unknown at this time	Case is up to you	Gasketless, weatherproof housing ABS plastic	Unknown at this time	ABS plastic
Camo	Realtree Hardwoods® HD™	NaturalGear® camo finish	Realtree Hardwoods® Green HD™ finish	Tree bark Reality® camo 3-D texturing	MothWing Camouflage	Camo is up to you	Yes	No , flat black or tan finish	Yes
Security Lock/Case	Steel Locking Bracket Available separately	Locking bracket with 2 cable holes supplied	Master Lock® Python™ cable	Security cable and internal screw hole	Yes, flange on case for padlock	Security cable with lock	Unknown at this time	Lockable cover	Optional locking bracket
Warranty	1 year	6 months parts and labor	Unknown at this time	Unknown at this time	60 days parts and labor warranty	You fix it since you made it	6 months to 1 year	1 year	1 year parts and labor
Street Price	\$649.99	\$650.00	\$599.99	\$499.99	\$549.99	\$200 to \$300	425.00	\$329 for camera and handheld monitor	\$349.99